



- 1 LED Light
- 2 LED Light Switch
- 3 Power Button
- BAR/PSI Unit Switch Button
- ⑤ Display

- 6 The Button for Presetting Tire Pressure
- ② Air Inflator Start-stop Button
- ® Type-C Charge Port / USB-A Discharge Port
- 9 EC8 Starting Port
- 10 Air Inflator Output Port

JUMP STARTER & AIR INFLATOR

Technical Specifications			
Model Number	JA300	JA301	JA302
Battery Capacity	45Wh	74Wh	76Wh
Starting Voltage	12V	12V	12V
Starting Current	800A	1000A	1200A
Peak Current	1500A	2000A	2500A
Pressure Range	10~150 psi	10~150 psi	10~150 psi
Sensor Accuracy	±2psi	±2psi	±2psi
Input	USB-C 5V/3A, 9V/2A	USB-C 5V/3A, 9V/2A	USB-C 5V/3A, 9V/2A
Output	USB-A 5V/3A, 9V/2A	USB-A 5V/3A, 9V/2A	USB-A 5V/3A, 9V/2A
Polarity	Red(+), Black(-)	Red(+), Black(-)	Red(+), Black(-)
Charging Temp	0°C to 45°C	0°C to 45°C	0℃ to 45℃
Operating Temp	-20℃ to 50℃	-20℃ to 50℃	-20℃to 50℃
Storage Temp	-20℃ to 50℃	-20℃ to 50℃	-20℃ to 50℃
Battery Life	>1000 cycles in good condition	>1000 cycles in good condition	>1000 cycles in good condition
Charging Time	3 to 6.5 Hours	4 to 7.5 Hours	4.5 to 8 Hours
Suitable Engine Displacement	Up to Gasoline 7L / Diesel 4.5L	Up to Gasoline 8L / Diesel 6L	Up to Gasoline 8.5L / Diesel 6.5L
Dimension	254*142*103mm	254*142*103mm	254*142*103mm
Net Weight	1.75kg	1.77kg	1.85kg
Certification	UL FCC CE RoHS UN38.3	UL FCC CE RoHS UN38.3	UL FCC CE RoHS UN38.3

12V Jump Starter

Test your car battery's voltage even in emergency situations, and jumpstart your car reliably.

Utilizing Grepow's high-quality batteries, this jump starter ensures reliability, safety, and power! Operation is efficient with the one-button push, and the BMS allows for a safer product.











Air Inflator

Portable air inflator without too many extra parts.

Ability to inflate from 10psi up to 150psi.

Great capacity and endurance: fill up at least 5 tires!









690