

MARSTEK

Power Anywhere & Anytime

MARSTEK M1200

Portable Powerstation

1800W AC Output, 1200W AC Input, 800W PV Input
1030Wh LFP Battery, Cycle Life ≥ 6000

USB-C1 100W, USB-C2 45W, USB-A1/A2 18W

Extra Battery Module (EBM)
1030Wh LFP Battery, Cycle Life ≥ 6000
Expand to 1 EBM, up to 2060Wh

HD TFT Display
Support Wi-Fi / Bluetooth

MARSTEK APP



Marstek Energy Co., Limited

Add: BLDG#A, Changfang Industrial Park, No.2 Guihua 5th Road, Pingshan District, Shenzhen, Guangdong, China

Tel: 86-755-28398778



Email: market@marstekenergy.com

Web: www.marstekenergy.com



Product Manual

Specifications



Model	M1200
GENERAL	
Capacity	1030Wh~2060Wh
Cell Chemistry	LiFePO ₄
Lifecycle	6000+ Cycles to 80% Capacity
Indicator	APP/TFT Screen
Storage Temp.	-50 °F~113 °F(-10 °C ~45 °C)
Operating Temp.	-50 °F~104 °F(-10 °C~40 °C)
Material	ABS + PC + Metal
Weight	13±0.5kg
Dimensions	400*195*200mm
Battery Management System	OVP,UVPOCP,SCPOTP,UTP etc
Solar Charge System	MPPT Charge Controller
INPUT	
AC	1000W Max(220V~240V@50Hz)/1000W Max(100V~120V@60Hz)
XT60	800W Max(Solar/DC 12~59V)
OUTPUT	
AC	1800W Max(220V~240V@50Hz)/1200W Max(100V~120V@60Hz)
USB-A	18W Max(5V~12V)
USB-C #1	100W Max
USB-C #2	45W Max
DC 5525	120W(12V/10A)
Car Charger	120W(12V/10A)



Model	P1200
GENERAL	
Capacity	1030Wh
Cell Chemistry	LiFePO ₄
Nominal Current	23A
Lifecycle	6000+ Cyclesto 80% Capacity
Storage Temp.	-4 °F~113 °F(-20 °C~45 °C)
Operating Temp.	14 °F~113 °F(-10 °C~45 °C)
Material	ABS + PC + Metal
Weight	13±0.5kg
Dimensions	400*195*200mm
Battery Management System	OVP,UVP,OCP,SCP,OTP,UTP,etc
INPUT	
Battery Voltage Range	42V~50.4V
Charge Voltage	50.4V
Charge Current	27A
OUTPUT	
Discharge Current	54A
DoD	90%